

Specifications Steeler Explorer 50



©Steeler Yachts reserves the rights to change prices and/or specifications without prior notice.

Index

1. GENERAL 7
Dimensions 6
Type of yacht 6
Construction 6
Propulsion 6
Classification 6
Inspection 6
Alterations during the building process 6
Checking, commissioning and test run 6
Conditions/insurance/transfer of ownership 7
Suppliers 7
Manuals and drawings 7
2. HULL- and SUPERSTRUCTURE CONSTRUCTION 8
Plate material 8
Combined profiles and stiffening 8
Trade profiles 8
Quality and welding 8
Specification of the materials 8
Longitudinal- and transverse reinforcement 8
Tanks 8
Waterproof partitions 9
Engine foundations 9
Bulwark 9
Rubbing strake 9
Water gutter pipes 9
Stern 9
Cockpit 9
3. PAINT SYSTEM 10
4. CATHODIC PROTECTION 10
5. SOUND AND VIBRATION INSULATION 10
In general 10
Absorbing 10
Insulation engine room 10
6. SAILING AND MANOUVERING 11

6.1 Propulsion installation	11
Main engine	11
Propeller shaft	11
Propeller shaft tube/socket.....	11
Propeller	11
6.2 Steering installation	11
6.3 Bow thruster	11
6.4 Navigation	11
7. FUEL SYSTEM	12
Fuel tanks.....	12
Tank volume meter.....	12
Fuel Filters.....	12
8. BILGE SYSTEM.....	12
Automatic bilge pumps.....	12
9. FRESHWATER SYSTEM	12
Freshwater tanks	12
Water Pressure System	12
Hot water System	12
10. WASTEWATER SYSTEM.....	13
Toilet installation	13
11. HEATING	13
Heating system	13
12. VENTILATION SYSTEM	13
Engine room ventilation	13
Bathroom.....	13
Interior	13
13. ELECTRICAL INSTALLATION.....	14
Digital Switching	14
230 V AC System	14
230 Volt Switchboard	14
Shore Power	14
Cords and Cables	14
Inverter/Battery Charger	14
24 VDC System.....	14
Batteries.....	14
Additional Battery Charger	14
24 VDC main switch box	15

24 VDC switch panel dashboard	15
Lighting, wall sockets and wiring	15
TV	15
Audio	15
Navigation lights	15
Signal horn	15
Windscreen wipers	15
14. INTERIOR, CARPENTRY	16
Design and construction carpentry	16
Domestic appliances	16
15. DOORS, WINDOWS AND PORTHOLES	16
Saloon/wheelhouse	16
Hull	16
Superstructure	16
Door in Saloon	16
16. EXTERIOR	17
16.1 Anchor system	17
Windlass	17
16.2 Flexiteek	17
16.3 Cockpit table	17
16.4 Nameplates	17
16.5 Guardrail	17
16.6 Bollards and cleats	17
16.7 Boarding ladder	17
16.8 Swimming ladder	17
16.9 Navigation mast	17
17. EQUIPMENT AND SAFETY	18
Mooring ropes	18
Fenders	18
Diesel	18
Flags	18
Fire extinguishing system	18
Floor engine room	18



1. GENERAL

Dimensions

Length	14,99 M
Length hull	14,65 M
Beam	4,76 M
Draft	1,25 M
Minimum clearance	3,10 M*
Displacement (50% loaded)	30 ton

*with folding mast

Type of yacht

Multi-chine hull with straight bow.

Construction

Grade A Steel hull, superstructure and construction

Propulsion

Deutz VD6, 6 cylinder in-line, water-cooled intercooling, 155 KW (210 HP) @ 2400 RPM.

Classification

The yacht is build according to CE classification – B/(A-optional)

Inspection

The principal, the inspector of the CE and the suppliers have access to all the building areas during opening hours to control the quality of all the parts.

Alterations during the building process

The shipyard has the obligation to build in accordance with the specification book and the drawings. Small changes which have no consequences for the price and delivery time are admitted, after consulting the architect and/or principal and provided that the quality remains.

Changes which have consequences for price, delivery time, weight or stability will only be executed after a written agreement between the principal and the shipyard.

Checking, commissioning and test run

1. All integrated bottom tanks are being pressure tested according to CE regulations.
2. All systems like electrical installation, fuel, bilge, waste water, fresh water installation, heating, hydraulic (optional) etc. will be tested intensively in the water and on shore.
3. All exterior windows, doors and opening will be tested watertight according to CE regulations.
4. On expense of the shipyard, who is responsible for the technical installation, a test run of at least 8 hours will be held in open water to check all systems.
The engines have to be tested at least 1 hours on full speed.
5. To achieve a horizontal and vertical trim with an unloaded ship, the shipyard is allowed to put in leaden breads till a maximum of 1000 kg, situated isolated, steady and seaworthy.

Conditions/insurance/transfer of ownership

During the building the general terms and conditions of the Hiswa apply, as mentioned at the District Court of law in Amsterdam on April 1th 2011 under number 040/2011.

Suppliers

All the rules of the suppliers will be followed exactly. If necessary the supplier will be asked to conduct inspections and when needed to install the equipment, so that the principal will be sure that the supplier has fulfilled his duty to guarantee.

Manuals and drawings

An instruction book with drawings will be delivered, according to the CE-standard with an index.

The electrical and system diagram-drawings will be delivered in a map with index, also according to the CE-standard.

2. HULL- and SUPERSTRUCTURE CONSTRUCTION

Plate material

Steel for the building of yachts, grade A, sandblasted SA2,5.

Combined profiles and stiffening

As plate material.

Trade profiles

Angle bar profiles and T-profiles are according to shipbuilding quality, sandblasted SA2,5.

Quality and welding

The welding is according to the highest standards of the Dutch shipbuilding.

Ship building requirements according ISO 12215/4 – Small craft – Hull construction and scantlings / part 4 : Workshop and manufacturing

Welding:

- MIG
- TIG
- All welders are Certified welders.

Plate thickness according to construction plans.

Specification of the materials

Keel plating	: 6/10 mm
Hull plating	: 5/6 mm
Decks (also above engine room)	: 4 mm
Bulwark inside	: 5 mm
Superstructure side's and front plating	: 4 mm
Wheelhouse and cabin roof plating	: 4 mm
Frame distance	: 400 mm

Longitudinal- and transverse reinforcement

Longitudinal reinforcement are located at:

- keel construction
- tank partitions
- pass on in the engine foundation
- cabin sole in front of engine room partition to the chain locker partition.

Transverse reinforcement by ribs with knees, accumulated web ribs, tans on each rib.

The longitudinal- and transverse reinforcement are built in such a way that the water always runs to the lowest point.

Tanks

Double bottom tanks are used for the fuel tanks, which are located in the engine room and front compartment. Tank walls and sling partitions each 4 mm. All fuel tanks are accessible through inspection covers.

Waterproof partitions

The Steeler Explorer 50 is constructed with three watertight compartments.

The bulkheads are being made in a continuous weld and are reinforced.

The watertight bulkheads are strengthened by T-profile.

Feed through of bulkheads are made with glands.

Locations of watertight compartments:

1. In front of forward cabin
2. Engine room
3. Storage compartment (aft of engine room)

Engine foundations

The foundation of the main engine is strengthened in order to minimize vibrations.

The space in the foundation is filled with fine sand, this reduces the vibrations in the ship caused by the engine(s).

Bulwark

Bulwark 5mm outside plate and 5 mm inside plate.

Rubbing strake

Alongside the hull plates there will be situated 2 rubbing strakes. This is a high and a low one at the swimming platform and stern. The high rubbing strake will be rejuvenated at the bow and completed at the stern. The lower rubbing strake profile goes from the swimming platform till frame 8.

Water gutter pipes

The anchor locker has stainless steel drain pipes, the sliding roof recess on top of the wheelhouse has two stainless steel drain pipes on port- and starboard side (optional). The deck water in the gangway and aft deck is collected in a water drain locker. This drain locker is positioned at the transition between aft deck and gangway and is drained overboard.

Stern

In the double curved stern integrated steps will be welded on port and starboard.

Cockpit

In the cockpit an U-shaped bench is welded. Within this bench storage lockers are situated.

3. PAINT SYSTEM

- Entire yacht is SA2,5 sandblasted.
- A 2-components AWL-Grip or AlexSeal painting system is applied:
 - Protective primer
 - Fairing compound
 - Finishing filler
 - Finish primer
 - Premium Topcoat
- Engine room in gloss topcoat.
- Different colour hull and superstructure
- The entire paint system will be applied accurate, professional and Dust-free according to high boat building standards.
- Each yacht is separately surveyed by an independent paint-job surveyor.

4. CATHODIC PROTECTION

The Steeler Explorer 50 anodes near the bow thruster, propeller shaft, propeller, rudder and at the bottom of the ship will be placed.

5. SOUND AND VIBRATION INSULATION

Standard isolation hull and superstructure with foam core insulation. Soundproofing floor in saloon.

In general

To silence and absorb sound and vibrations as much as possible, all the engines, pumps, fans etc. will be set up flexible with hose connections connected to the pipes.

Absorbing

A sandwich construction consisting of sandwich plates, with a special layer of lead are mounted under the floors above the engine room.

Insulation engine room

Engine room insulated with Sonitech insulating panelling.

6. SAILING AND MANOUVERING

6.1 Propulsion installation

Main engine

Deutz VD6, in-line, 6 cylinder, water-cooled intercooling, 155 KW (210 HP) by 2400 RPM.
Optional different engines depending on customers wishes can be installed.

- Direct injection, water-cooled turbocharger, water in fuel alarm.
- Fresh water cooling by centrifugal fresh water pump
- Sea water cooling by rubber impeller seawater pump
- Alternator, 24 volt – 80 amps

Gearbox

- ZF63A gearbox
- Flexible coupling
- Flanged to engine
- Gearbox supports for flexible mounting

Propeller shaft

Stainless steel duplex shaft.

Propeller shaft tube/socket

Water lubricated propeller shaft installations will be installed.

Propeller

Bronze propeller, protected by keel-sole.

6.2 Steering installation

Steel rudder, with NACA profile.

Stainless steel rudder shaft and levers.

A complete steering installation with steering pump and hydraulic cylinder is installed.

6.3 Bow thruster

A SidePower 150 KGF proportional electric bow thruster is installed.
(Hydraulic optional)

6.4 Navigation

The yacht is equipped with the following navigation instruments:

- NSS EVO 3 12 inch multifunctional display
- RS90 VHF
- IS 42(Depth Speed Temperature)

7. FUEL SYSTEM

Fuel tanks

Integrated fuel tanks with a total capacity of approx. 1300 litres are installed. Divided over two tanks situated in the engine room.

In the port-side gangway 1 filler cap is placed.

Tank volume meter

A tank measuring system with a digital reading of the equipment is placed in the cockpit.

Fuel Filters

A double fuel filter/ water separator is installed for means of redundancy. In addition the double filter is equipped with a water-in-fuel alarm.

8. BILGE SYSTEM

Automatic bilge pumps

Three 24V automatic bilge pumps with a capacity of approx. 65L/min are installed. The pumps are located in the engine room, in the foreship and in the aft side of the yacht.

Pumps are automatically connected outside the 24V main switch. The drain tube of the pumps are connected with the ventilated overboard pipes.

A manual bilge pump is delivered

9. FRESHWATER SYSTEM

Freshwater tanks

One Polyethylene freshwater tank with a total capacity of approx. 1000 litres is installed in front of the ship under the cabin floor.

The tank is supplied with a filling pipe, hose and cap, which are situated in the port-side gangway and a ½" ventilation pipe with gooseneck. On the water tank a tank measuring system is installed with a read-out in the wheelhouse.

Water Pressure System

A Water pressure system, with an approximate capacity of 55 litres/min is installed.

Hot water System

The Webasto, Isotemp boiler, type B75 completely stainless steel. The boiler is provided with a built-in tap water supply. Flue gases from the kettle run through the silencer, gooseneck and heat isolating skin grommet to the outside.

(optional KABOLA HR400 central heating system for heating and hot water supply)

10. WASTEWATER SYSTEM

The yacht is equipped with a 400 litre Polyethylene wastewater tank. All wastewater from the toilets is collected in this tank. The tank can be emptied automatically with a pump, which pumps the water overboard. An additional possibility is to discharge the wastewater tank in a marina through a dockside discharge.

The drain of the kitchen through three-way tap, directly overboard or to the above mentioned tank.

All wastewater drains of the washing bowls, shower etc. are pumped directly overboard. The wastewater from the shower is collected in a drainstation and is pumped overboard.

All blackwater pipes are odor proof.

Toilet installation

One Planus toilet is installed, 24V, Multi, soft closing.
All-in-one panels are installed for flush operation.

11. HEATING

Heating system

Webasto heating system 2x 5 kW of the type: Webasto Air Top Evo 55, 24Volts.

With exhaust outlets in every compartment throughout the interior.

All wet cells will have a design radiator.

12. VENTILATION SYSTEM

Engine room ventilation

Integrated ventilation grills portside and starboard in the superstructure.

Bathroom

The bathroom is equipped with forced ventilation.

Interior

Entire interior is ventilated.

13. ELECTRICAL INSTALLATION

The Electrical installation is executed according to the standards for the luxury yacht building. The electrical system has been designed to meet an estimated daily use and moderate charging times.

Digital Switching

Electrical system is installed with Empirbus/CANbus digital switching system, with 4 Empirbus modules (64 i/o channels).

System monitoring and operation through 10" touchscreen display mounted near helm station.

230 V AC System

The 230 V AC system is a single phase.

230 Volt Switchboard

A 230 volt switchboard is installed in the storage. Board fully equipped to switch over to shore power, alternator and 230 V converter, automatic fuses for the 230 v system, measuring instruments for the voltage and ampere, a RCD and 3 control lights.

Shore Power

The shore connection will be only run from charger to shore. Shore power will not be directed to any sockets or users directly. This to prevent corrosion.

The shore connection will be placed in the cockpit.

The shore power exists off (Mastervolt):

Galvanic isolation transformer 3600VA / 16A

Shorepower connection 16A, with stainless steel cover

Shorepower connection cable, 16A - 15m

Cords and Cables

All cords and cables are made of copper with a PVC insulation and connections by means of tinned lugs.

Inverter/Battery Charger

A Mastervolt Mass Combi Pro 24/3500 - 100 Ah is installed. Input 24 VDC, output 230 VAC.

24 VDC System

The 24VDC system has double poles and is free of grounding.

Batteries

6 x 225 Ah main batteries, 2x 90 Ah. starting circuit and 2x 225 Ah. bow thruster. All batteries are from Mastervolt and are AGM maintenance free. All batteries are fastened with straps in a welded construction.

Additional Battery Charger

A Mastervolt, type Chargemaster 24/30 - 3 outputs proportionally controlled battery charger will be installed in the engine room.

24 VDC main switch box

A 24 VDC switch box will be installed complete with an auxiliary switch, diode, Volt – and Ampere meter, automatic fuses for six lighting groups, automatic circuit breakers for 24 Volt users and three reserve groups.

24 VDC switch panel dashboard

A 24 VDC switch panel with switches for the windscreen wipers, navigation lighting, horn etc. will be installed near the dashboard.

Lighting, wall sockets and wiring

Light plan is upon customer wishes

Standard: Luxurious LED lighting 34x, dimmer for saloon lightning, bedside lights LED, 4x.

TV

On a location of choice a 43 inch TV is installed on a tv-elevator.

Audio

Fusion FM/DVD/USB/Bluetooth + 4 speakers

Navigation lights

LED navigation lights in accordance with international requirements.

The positions of the navigation lights are the following:

- 1 navigation light starboard
- 1 navigation light portside
- 1 stern light
- 1 combination anchor light/ steam light

Signal horn

Signal horn is located in the mast.

Windscreen wipers

2 double armed windscreen wipers will be mounted, a 24 Volt electric windscreen wiper, type ES, manufactured by Speich with synchronic interval (Speich dual control) with parallel arm and wiper.

14. INTERIOR, CARPENTRY

The interior lay-out is based upon customer wishes.

Design and construction carpentry

The interior will be built upon customer requirements: the standard specifications include 2 cabins with owners cabin in the front, different types of wood standard, luxurious upholstered panels, luxurious salon and cockpit table, Metroflor PVC flooring, full upholstery entire yacht including cockpit cushions (Steeler Collection), captain's chair, luxurious mattresses, stainless steel door fittings, stainless steel cabinet fittings and stainless steel hatch fittings.

Standard equipped with 1x wet cells with shower and toilets (electrical toilets), stainless steel sink unit, one handle mixer tab, shower with mixer tab and luxurious Corian Work surface.

Domestic appliances

Standard the galley is equipped with Luxurious Corian Work surface, Stainless steel sink unit, one handle mixer tab, 4-ring gas stove (Siemens), downdraft cooker fan, 130 litre fridge with freeze unit, combi oven/microwave (Siemens), waste bin.

15. DOORS, WINDOWS AND PORTHOLES

Saloon/wheelhouse

Insulated (partially curved) double glass.

Hull

- 2 x Insulated tinted panorama windows in hull (high-impact resistant)
- 6 x Opening aluminium portholes with mosquito screens in hull recess

Superstructure

- 1x Flush opening hatch with mosquito screen and blind.

Door in Saloon

Aluminium entrance doors to saloon and wheelhouse, 3-pcs folding with insulated glass

16. EXTERIOR

16.1 Anchor system

- 35 kg stainless steel polished anchor
- 60 metre galvanised 10 mm anchor chain

Windlass

Electric windlass 24VDC with deck push buttons.

16.2 Flexiteek

Standard equipped with Flexiteek on the cockpit floor.

16.3 Cockpit table

A luxurious cockpit table is fitted on stainless steel pedestal.

16.4 Nameplates

On both sides of the yacht Steeler logo and type of the yacht will be fitted in stainless steel.
On the stern in stainless steel character's name of the vessel will be placed.
The characters will be high-polish finished.

16.5 Guardrail

On the hull around the foredeck and gangways a guardrail will be placed.
Rail stanchions and rail made of 42,5 mm stainless steel tubes. Steel construction under stanchions is reinforced. Amidships on port and starboard a rail opening is located.

16.6 Bollards and cleats

All cleats stainless steel 316.
In total 4 fixed cleats and 4 double bollards with rubbing plats under the cleats and bollards will be fitted.

16.7 Boarding ladder

A stainless steel 316 boarding ladder will be delivered.
The boarding ladder is detachable and to be stowed away in the storage.

16.8 Swimming ladder

A fixed swimming ladder is mounted at the stern of the yacht.

16.9 Navigation mast

Teak Wooden mast in front of the wheelhouse. Mast is manually foldable.

17. EQUIPMENT AND SAFETY

Mooring ropes

4 Luxurious mooring ropes, black, length 15m, 16mm.
The mooring ropes will be provided with an eye on one side.

Fenders

Six black fenders, diameter ca. 30cmx90cm height, each with an eye on each side and 12mmx2,5m luxurious nylon lines.

Diesel

The yacht is delivered with 600 litres diesel.

Flags

Pulpit equipped with a stainless steel jack staff (brace), holder and flag.
Near the stern a stainless steel flagstaff holder will be placed with a stainless steel flagstaff and national flag.

Fire extinguishing system

In the engine room an automatic fire extinguishing systems installed.
Three portable fire extinguishers, 2 kg. with holders installed by arrangement with customer.

Floor engine room

In the engine room and in the storage an aluminium diamond plate/ checker plate floor will be placed.